

## QuickSeam™ Batten Cover Strip

### 1. Description

The Firestone QuickSeam™ Batten Cover Strip is a 152 mm wide (6") semi-cured EPDM strip laminated to a QuickSeam tape. The strip is used to cover and seal batten strips which are installed over the membrane, as specified in the Firestone guidelines.



### 2. Preparation

The RubberGard™ EPDM surfaces and attachment components within the seaming area must be prepared with QuickPrime™ Plus, using a QuickScrubber™ or QuickScrubber™ Plus tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

### 3. Application

Centre the Cover Strip over the batten strip. Cover Strip should not overlap at T-junctions. Refer to the Firestone guidelines for specific installation instructions.

### 4. Coverage

In accordance with length of batten strip to be covered. Provide an overlap of 75 mm minimum at the begin/end of the batten strip. Adjoining QuickSeam Batten Cover strips require an overlap of 25 mm and a QuickSeam FormFlash cover patch.

### 5. Characteristics

Technical		
	EPDM Flashing	QuickSeam Tape
• Base	EPDM	Rubber polymers
• Color	Black	Black
• Solvents	None	None
• Solids	100%	98%
• State	Semi-cured	Cured
• Thickness	1.0 mm	0.8 mm
• Width	152 mm	156 mm

### 6. Packaging / Storage / Shelf Life

Packaging	30.5 m (100') rolls, 2 rolls per carton
Part number	W56RAC1616

*Note: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.*

**Storage:** Store in original unopened containers at temperatures between 15°C and 25°C, in a well-ventilated place. Keep the material dry and out of direct sunlight until ready for application.

**Shelf Life:** 12 months can be expected if stored in above-mentioned conditions. Verify production date on each roll. Shelf life will be reduced if exposed to higher temperatures. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories.

### 7. Precautions

Refer to Safety Data Sheet.

This document replaces any other document published previous. This sheet is meant to highlight Firestone product information based on latest knowledge and experience and is subject to change without notice (check the Firestone website for latest document version). Above mentioned values are based on tested samples and may vary within applicable tolerances. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. No Firestone representative is authorized to vary this disclaimer.