# **Safety Data Sheet ULTRABOND ECO S 968 1K**

Safety Data Sheet dated 3/25/2019 version 1



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Mixture identification:

Trade name: ULTRABOND ECO S 968 1K

Trade code: 9007431

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Sililated polyurethane adhesive

Uses advised against: Data not available

### 1.3. Details of the supplier of the safety data sheet

Company: MAPEI S.p.A. - Via Cafiero, 22 - 20158 Milano

Tel: +39-02-376731 Fax: +39-02-37673.214

Responsable: sicurezza@mapei.it 1.4. Emergency telephone number

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39/02/66101029

MAPEI S.p.A. - Tel. +(39)02376731 - (office hours)

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Regulation (EC) n. 1272/2008 (CLP)

The product is not classified as hazardous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

### 2.2. Label elements

The product is not classified as hazardous according to Regulation EC 1272/2008 (CLP).

### **Special Provisions:**

EUH210 Safety data sheet available on request.

## Contains:

Reaction mass of Bis(1,2,2,6,6pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

May produce an allergic reaction.

## Special provisions according to Annex XVII of REACH and subsequent amendments:

None

### 2.3. Other hazards

No PBT/vPvB Ingredients are present

Other Hazards: No other hazards

Further hazards:

Methanol is released by hydrolysis during application.

# SECTION 3: Composition/information on ingredients

## 3.1. Substances

N.A.

### 3.2. Mixtures

Mixture identification: ULTRABOND ECO S 968 1K

# Hazardous components within the meaning of the CLP regulation and related classification:

Quantity Ident. Numb. Classification **Registration Number** Name ≥2.5 - <5 % Flam. Liq. 3, H226; Acute Tox. 4, 01-2119513215-52-xxxx CAS:2768-02-7 vinyltrimethoxysilane

EC:220-449-8

4/15/2019 **Production Name** ULTRABOND ECO S 968 1K Date Page n. 1 of 8 Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

EC:915-687-0 Skin Sens. 1, H317; Aquatic Acute 01-2119491304-40-xxxx 1, H400; Aquatic Chronic 1, H410, M-Chronic:1

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

# 4.2. Most important symptoms and effects, both acute and delayed

N.A.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treatment: N.A

(see paragraph 4.1)

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

## 5.3. Advice for firefighters

Use suitable breathing apparatus.

## **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

# 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

### 6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

#### 6.4. Reference to other sections

See also section 8 and 13

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

# 7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

## 7.3. Specific end use(s)

Recommendation(s)

Date 4/15/2019 Production Name ULTRABOND ECO S 968 1K Page n. 2 of 8

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# **Predicted No Effect Concentration (PNEC) values**

Component	CAS-No.	PNEC LIMIT	Exposure Route	Exposure Frequency	Remark
vinyltrimethoxysilane	2768-02-7	0,36 mg/l	Fresh Water		
		0,036 mg/l	Marine water		
		2,4 mg/l	Intermittent release		
		0,29 mg/kg	Freshwater sediments		
		0,048 mg/kg	Soil		
		6,6 mg/l	Microorganisms in sewage treatments		
Reaction mass of Bis(1,2,2,6,6- pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate		0,0022 mg/l	Fresh Water		
		0,00022 Marine water mg/l			
		0,009 mg/l	Intermittent release		
		1,05 mg/kg	Freshwater sediments		
		0,11 mg/kg	Marine water sediments		
		0,21 mg/kg	Soil		
		1 mg/l	Microorganisms in sewage treatments		

# **Derived No Effect Level. (DNEL)**

Component	CAS-No.		Worker Profess ional		Exposure Route	Exposure Frequency Remark
vinyltrimethoxysilan e	2768-02-7	0,2 mg/kg		0,1 mg/kg	Human Dermal	Short Term, systemic effects
		2,6 mg/m3		0,7 mg/m3	Human Inhalation	Long Term, systemic effects
		0,69 mg/kg		0,1 mg/kg	Human Dermal	Long Term, systemic effects
		2,6 mg/m3		0,7 mg/m3	Human Inhalation	Short Term, systemic effects
				0,1 mg/kg	Human Ora	Long Term, systemic effects
Reaction mass of Bis(1,2,2,6,6- pentamethyl-4-		2,5 mg/kg		1,25 mg/kg	Human Dermal	Short Term, systemic effects
Date 4/15/2019	Produ	uction Nam	ne UI	LTRABON	D ECO S 968	1K

2,35 mg/m3	0,58 mg/m3	Human Inhalation	Short Term, systemic effects
2,35 mg/m3	0,58 mg/m3	Human Inhalation	Long Term, systemic effects
2,5 mg/kg	1,25 mg/kg		Long Term, systemic effects
	1,25 mg/kg	Human Ora	Short Term, systemic effects
	1,25 mg/kg	Human Ora	Long Term, systemic effects

### 8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Suitable materials for safety gloves; EN 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

In case of insufficient ventilation use mask with AX filters (EN 14387).

N.A.

Hygienic and Technical measures

N.A.

Appropriate engineering controls:

N.A.

### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance and colour: paste beige

Odour: characteristic Odour threshold: N.A.

pH: N.A.

Melting point / freezing point: N.A.
Initial boiling point and boiling range: N.A.

Flash point: 62 °C (144 °F) Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.
Vapour pressure: N.A.
Relative density: N.A.

Solubility in water: Insoluble

Partition coefficient (n-octanol/water): N.A. - This product is a mixture

Auto-ignition temperature: N.A. - No explosive or spontaneous ignition in contact with air at room temperature

 $\label{eq:decomposition} \mbox{Decomposition temperature: } \mbox{ N.A.}$ 

Viscosity: 350,000.00 cPs

Explosive properties: N.A. - No components with explosive properties

Oxidizing properties: N.A. - No component with oxidizing properties

Solid/gas flammability: N.A.

### 9.2. Other information

No additional information

 Date
 4/15/2019
 Production Name
 ULTRABOND ECO S 968 1K
 Page n. 4 of 8

## SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Stable under normal conditions

#### 10.2. Chemical stability

Stable under normal conditions

## 10.3. Possibility of hazardous reactions

None

#### 10.4. Conditions to avoid

Stable under normal conditions.

#### 10.5. Incompatible materials

None in particular.

#### 10.6. Hazardous decomposition products

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

## Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

### Toxicological information on main components of the mixture:

vinyltrimethoxysilane

a) acute toxicity

LD50 Oral Rat = 7178 mg/kg

LD50 Skin Rabbit = 3200 mg/kg

LD50 Inhalation Rat = 16,8 mg/l 4h

e) germ cell mutagenicity NOAEL Inhalation Vapour Rat = 1,7 mg/l

NOAEC Inhalation Vapour Rat = 0,058 mg/l

28 d

g) reproductive toxicity

NOAEL Oral Rat = 1000 mg/kg

i) STOT-repeated

exposure

NOAEC Oral Rat = 62,5 mg/kg

Reaction mass of

a) acute toxicity

LD50 Oral Rat = 3230 mg/kg

Bis(1,2,2,6,6pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4piperidyl sebacate

#### If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

## **SECTION 12: Ecological information**

# 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

#### List of components with eco-toxicological properties

Quantity Component Ident. Numb. **Ecotox Infos** 

>=2.5 - <5 % vinyltrimethoxysilane CAS: 2768-02-7 a) Aquatic acute toxicity: LC50 Fish = 191 mg/L 96

Date 4/15/2019 **Production Name** ULTRABOND ECO S 968 1K Page n. 5 of 8

a) Aquatic acute toxicity: EC50 Daphnia = 169 mg/L 48

a) Aquatic acute toxicity: NOEC Daphnia = 28 mg/L - 21 d

a) Aquatic acute toxicity: NOEC Algae = 25 mg/L 72 a) Aquatic acute toxicity: EC50 Daphnia = 20 mg/L 24

>=0.1 - <0.25 % Reaction mass of Bis(1,2,2,6,6-**EINECS: 915**pentamethyl-4-piperidyl) sebacate 687-0

and Methyl 1,2,2,6,6-pentamethyl-

4-piperidyl sebacate

a) Aquatic acute toxicity: EC50 Algae = 0,22 mg/L 72

a) Aquatic acute toxicity: LC50 Fish = 0,97 mg/L 96

a) Aquatic acute toxicity: LC50 Fish = 7,9 mg/L 96 a) Aquatic acute toxicity: LC50 Fish = 0,9 mg/L 96

b) Aquatic chronic toxicity: NOEC Daphnia = 6,3 mg/L - 21 d

Page n. 6 of 8

#### 12.2. Persistence and degradability

## 12.3. Bioaccumulative potential

N.A.

### 12.4. Mobility in soil

NΑ

#### 12.5. Results of PBT and vPvB assessment

No PBT/vPvB Ingredients are present

#### 12.6. Other adverse effects

N.A.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

# **SECTION 14: Transport information**

Not classified as dangerous in the meaning of transport regulations.

#### 14.1. UN number

N.A.

## 14.2. UN proper shipping name

### 14.3. Transport hazard class(es)

N.A.

## 14.4. Packing group

### 14.5. Environmental hazards

N.A.

# 14.6. Special precautions for user

Road and Rail (ADR-RID):

N.A.

Air (IATA):

N.A. Sea (IMDG):

N.A.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC):

N.A.

PRODUCT REGISTER NUMBER: NA

Date 4/15/2019 **Production Name** ULTRABOND ECO S 968 1K MAL KODE: NA

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU)2015/830

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP) Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

#### German Water Hazard Class.

N.A.

Code

H226

4.1/C1

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 40

Restrictions related to the substances contained: 69, 70

#### **SVHC Substances:**

No Data Available

### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

### **SECTION 16: Other information**

Description

Flammable liquid and vapour.

	·				
H317	May cause an allergic skin reaction.				
H332	Harmful if inhaled.				
H400	Very toxic to aquatic life.				
H410	Very toxic to aquatic life with long lasting effects.				
Code	Hazard class and hazard category	Description			
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3			
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4			
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1			
4 4 4 4 4					
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1			

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

Chronic (long term) aquatic hazard, category 1

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Aquatic Chronic 1

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures) BCF: Biological Concentration Factor

 Date
 4/15/2019
 Production Name
 ULTRABOND ECO S 968 1K
 Page n. 7 of 8

BEI: Biological Exposure Index BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

 ${\it CLP: Classification, Labeling, Packaging.}$ 

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

VOC: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

 Date
 4/15/2019
 Production Name
 ULTRABOND ECO S 968 1K
 Page n. 8 of 8