



Cross line laser with 1 green horizontal line and 2 vertical lines (= plumb line above and below + 1 angle of 90°). Each line has 11 small laser points for improved visibility, even in a bright environment or outside. Pendulum levelling accurate to 1.5 mm/10 m and a range of 50 m with receiver (optional). Fine adjustment rotates laser precisely around the plumb line. Li-Ion battery with AC adapter/charger. Can also be used with 4 AA batteries.

Main specifications

Visibility	
Precision	1,5mm / 10m
Range (with receiver)	2x 50m
Dust and water tightness	IP54
Batteries	LI-ION (included) or 4x AA
AC power connector	✓
Levelling	Pendulum levelling

Power supply and batteries

AC power connector	✓
Charger integrated into AC power connector	✓

Dimensions

Dust and water tightness	IP54
DxWxH device	117 x 116 x 177 mm
Weight of device	0,79 kg
DxWxH box	259 x 257 x 282 mm
Weight box	2,53 kg

Detailed specifications

Plumb bob	✓
Number of laser dots per line	11
Number of 90° angles	1
Number of 45° angles	0
Revolutions per minute	Not applicable
Scan function	✗
Wind function	✗
Tilt function	✗
Self-levelling range	±2°
Slope function	✗
Maximum settable slope (X-axis/Y-axis)	Not applicable
Remote control	✗
Built-in screw for tripod	5/8"
Pendulum lock (for manual slopes)	✗
Transport security for the pendulum	✓
Number of laser diodes	3
Laser frequency (in receiver mode)	10KHz
Laser class	Class 3R - 510-530NM - >1mW / <5mW

IN THE BOX



048.03



HCASE



180.20



180.40



130.07



H60024



H60022



H60030

ACCESSORIES

Tripods



090.180

Tripod Light Duty 180cm
- 5/8



090.300

Tripod Medium Duty
300cm - 5/8"



120.330

Telescopic Tripod 330cm
- 5/8

Receivers



043.130.LTG

Smart BASE Green



150.11.LTG

Line Tracer 2 Green



150.12.LT

Line Tracer Red/Green



150.40.A

Quattro

Wall mounts



130.03

Wall mount Precision
5/8"



130.04

Wall mount Heavy Duty
5/8"